

CONCRETE MIXER

BIG CONCRETE MIXER



GENERAL INFORMATION

The Big model with inverse rotation is particularly suitable for concretes or mixes with large diameter inert particles, permitting rapid production times. Machines for medium-sized building site production, particularly sturdy and extremely easy to handle, these are typical ready-to-use machines quickly put in place when needed. All machines are fitted with hydraulic controls for easy drum and skip loading operation, the electrical equipment is hermetically enclosed in a special box and easy to inspect and the scraper blade is connected via a low voltage system.



CHARACTERISTICS

- Two cylinder Diesel engine
- Electric engine starting
- Hydraulic bucket lift piston
- Safety valve to prevent bucket falling onto piston
- Pneumatic wheels and height-adjustable legs
- Water tank with level indicator
- Side netting protection
- Available in version with 4 pneumatic wheels

Technical data	U.M.	500	750	1000	1200	1500
tank capability	lt	490	650	710	1100	1300
yield	lt	350	450	510	780	950
water tank capacity	n°	80	80	100	100	100
electrical engine power	Hp	5,5	7,5	10	10	15
diesel engine power	Hp	19	19	19	28	28
shovel's electric engine	Hp	2,5	2,5	2,5	2,5	2,5
length	cm	290	320	350	350	380
width	cm	190	190	190	220	220
height	cm	370	370	370	380	380
weight without shovel	Kg	1250	1300	1450	2400	2600