

DIN EN 1065 PROPS D CLASS



Extension (m)	D 30		D 35		D 40		D 55	
	It up (kN)	It down (kN)	It up (kN)	It down (kN)	It up (kN)	It down (kN)	It up (kN)	It down (kN)
5,50							20,60	23,15
5,40							21,65	24,60
5,30							22,75	26,00
5,20							23,85	27,45
5,10							24,95	28,85
5,00							26,00	30,25
4,90							27,10	31,70
4,80							28,60	34,10
4,70							30,20	36,70
4,60							31,80	38,45
4,50							33,40	38,45
4,40							34,95	38,45
4,30							36,55	38,45
4,20							38,25	38,45
4,10							38,45	38,45
4,00					21,10	24,70	38,45	38,45
3,90					22,50	26,80	38,45	38,45
3,80					23,90	28,95	38,45	38,45
3,70					25,35	30,95	38,45	38,45
3,60					26,75	30,95	38,45	38,45
3,50			24,20	27,75	28,00	30,95	38,45	38,45
3,40			25,70	27,75	29,15	30,95	38,45	38,45
3,30			27,15	27,75	30,35	30,95	38,45	38,45
3,20			27,75	27,75	30,95	30,95	38,45	38,45
3,10			27,75	27,75	30,95	30,95	38,45	38,45
3,00	20,60	24,20	27,75	27,75	30,95	30,95		
2,90	22,20	26,95	27,75	27,75	30,95	30,95		
2,80	23,80	29,65	27,75	27,75	30,95	30,95		
2,70	25,40	32,40	27,75	27,75	30,95	30,95		
2,60	26,40	35,55	27,75	27,75	30,95	30,95		
2,50	27,20	38,45	27,75	27,75	30,95	30,95		
2,40	28,00	38,45	27,75	27,75	30,95	30,95		
2,30	29,30	38,45	27,75	27,75	30,95	30,95		
2,20	30,90	38,45	27,75	27,75				
2,10	32,50	38,45	27,75	27,75				
2,00	35,05	38,45	27,75	27,75				
1,90	38,45	38,45						
1,80	38,45	38,45						

1kN = 102 kg



		D 30 ECO	D 30	D 35	D 40	D 55
ø int.	mm	48,30	63,50	63,50	63,50	76,10
Thickness	mm	3,20	2,60	2,70	2,80	2,90
ø est.	mm	60,30	76,10	76,10	76,10	88,90
Thickness	mm	2,60	2,60	2,60	2,60	2,60
Plate	mm	120 x 120 x 8	120 x 120 x 8	120 x 120 x 8	120 x 120 x 8	120 x 120 x 8
Weight	kg	16,50	17,40	19,85	22,46	33,00