

CONCRETE MIXER

CONCRETE MIXER NEW



GENERAL INFORMATION

Traditional and professional machine, built with the classic and reliable iron cast gear transmission and poly-V belt transmission



CHARACTERISTICS

- Single-phase motor 230V/50 Hz (except mod. 500)
- Silenced transmission switch with IP 55 minimum voltage coil, thermal protection and IP 67 EEC plug
- Mushroom emergency stop push button
- Poly-V belt transmission with belt tightener
- Steel drum built in 3 parts
- Semi pneumatic rubber wheels with steel rims
- Approved drawbar for handling
- Available on request with 380V/50 Hz motor (except mod. 180)
- Available on request con petrol and diesel engines (mod. 180 gasoline only)

Technical data	U.M.	180	250	320	350	500
tank capability	lt	180	250	300	350	500
yield	lt	150	190	250	300	430
mixture per hour	n°	26	26	26	26	26
electrical engine power	Hp	0,75	1,5	1,5 / 2	1,5 / 2	2
gasoline engine power	Hp	2,8	3,9 / 6	3,9 / 6	3,9 / 6	3,9 / 6
diesel engine power	Hp	-	6,8 / 7,5	6,8 / 7,5	6,8 / 7,5	6,8 / 7,5
weight	Kg	115	200	208	210	290
length	cm	154	183	183	183	197
width	cm	81	92	92	92	115
height	cm	130	145	145	145	163
Lpa g	db	78	77	77	77	77
Lpa peak g	db	< 130	< 130	< 130	< 130	< 130