

"DIN EN 1065 CLASS D" PROPS LOADS TABLE – ECO

1kN=102kg

Extension	D 25 ECO (1,46 - 2,50 m)		D 30 ECO (1,82 - 3,00 m)		D 35 ECO (2,10 - 3,50 m)	
	Up	Down	Up	Down	Up	Down
(m)	(kN)	(kN)	(kN)	(kN)	(kN)	(kN)
3,50	-	-	-	-	20,60	24,10
3,40	-	-	-	-	20,90	24,80
3,30	-	-	-	-	21,30	25,40
3,20	-	-	-	-	21,70	26,00
3,10	-	-	-	-	22,20	26,70
3,00	-	-	21,10	25,30	22,70	27,40
2,90	-	-	23,10	27,70	23,30	28,30
2,80	-	-	24,80	29,80	24,00	30,00
2,70	-	-	27,00	32,40	24,60	31,10
2,60	-	-	28,90	34,70	25,30	32,30
2,50	20,20	24,80	30,60	36,70	26,00	34,00
2,40	21,30	27,20	32,10	38,50	26,70	35,20
2,30	22,50	29,50	34,00	39,00	27,50	37,50
2,20	23,30	31,90	36,80	39,00	28,50	39,00
2,10	24,00	34,30	39,00	39,00	30,00	39,00
2,00	24,60	36,70	39,00	39,00	-	-
1,90	25,80	36,70	39,00	39,00	-	-
1,80	26,90	36,70	39,00	39,00	-	-
1,70	28,40	36,70	-	-	-	-
1,60	30,10	36,70	-	-	-	-
1,50	31,80	36,70	-	-	-	-