


## PODPORY DIN EN 1065 KLASA E

OTWARCIE	E 30 1,80 - 3,00 m		E 35 2,00 - 3,50 m		E 40 2,30 - 4,00 m		
	IT UP	IT DOWN	IT UP	IT DOWN	IT UP	IT DOWN	
( metrów )	( kN )						
4,0					33,2	36,5	
3,9					36,8	40,5	
3,8					39,0	41,0	
3,7							
3,6							
3,5			32,0	33,6			
3,4			35,3	37,1			
3,3			37,7	39,6			
3,2			40,0				
3,1			41,0	41,0	41,0		41,0
3,0	32,4	35,6					
2,9	35,8	39,4					
2,8	36,4	40,0					
2,7	37,3						
2,6	38,8						
2,5	39,7						
2,4	40,0						
2,3	41,0	41,0					
2,2							
2,1							
2,0							
1,9							
1,8							



## GBM Building Equipment

		E 30	E 35	E 40
<b>MAKSYMALNE PRZEDŁUŻENIE</b>	cm	300	350	400
<b>MINIMALNE PRZEDŁUŻENIE</b>		173	198	225
<b>Ø WEWNĘTRZNE</b>	mm	63,50		76,10
<b>Ø ZEWNĘTRZNY</b>		76,10		88,90
<b>WAGA</b>	Kg	17,5	23,80	26,00